



EXPLOSION RELIEF CURB MOUNTED SKYLIGHT

MODEL: ERS-CM-1-FTH-IR-HW-MF

NOT TO SCALE

ERS - EXPLOSION RELIEF SKYLIGHT
 CM-CURB MOUNTED
 1-SINGLE GLAZED
 FTH - FIBERGLASS TRANSLUCENT HIGH
 IR - IMPACT RESISTANT
 HW - HIGH WIND
 MF - MILL FINISH

MODEL SIZE	INSIDE CURB DIMENSIONS	QTY
4848	48" x 48"	
4896	48" x 96"	

DOME MATERIAL TESTED IN CONFORMANCE WITH:

- HIGH WIND RESISTANT - DOME OF THIS UNIT HAS EXCEEDED 90 MPH UPLIFT IN TESTING.
- BURN RATE - CLASSIFIED AS CC1 MATERIAL.
- TESTED AND MET LOAD REQUIREMENTS PER OSHA 29 CFR 1910.23 (e) (8).
- TESTED AND MET REQUIREMENTS AS DESCRIBED IN "STANDARD PRESENTATION TO CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH STANDARDS BOARD - PROPOSED STATE STANDARD, TITLE 8, CHAPTER 4, SECTION 1632 (REPORT NUMBER 3075015-2).
- TESTING PERFORMED ON 48"x96" DOME.

Bristolite® Daylighting Systems

401 East Goetz Avenue, Santa Ana, CA. 92707
 TEL 714.540.8950 / FAX 714.540.5415

CUSTOMER :

PROJECT :

PREPARED BY :

SUBMITTAL DATE :

JOB NO :

ARCHITECT :