

ENERGY STAR CURB MOUNTED SMOKE HATCH W/EXTERIOR MANUAL RELEASE

* FUSIBLE LINK TEMPERATURE

PLEASE SELECT ONE:

212° O SHD - ALUMINUM SMOKE HATCH IR - IMPACT RESISTANT

> HW- HIGH WIND M1 - EXTERIOR MANUAL RELEASE

MF - MILL FINISH

286° O

360° ○

MODEL NUMBER	INSIDE CURB DIMENSIONS	QTY
F4848-SHD-CM	48"x48"	
E4896_SHD_CM	48"v96"	

NOT TO SCALE

MODEL: FXXXX-SHD-CM-1-FTH-IR-HW-M1-MF

DOME MATERIAL TESTED IN CONFORMANCE WITH:

- HIGH WIND RESISTANT DOME OF THIS UNIT HAS EXCEEDED 90 MPH UPLIFT IN TESTING.
- BURN RATE CLASSIFIED AS CC1 MATERIAL.
- TESTED AND MET LOAD REQUIREMENTS PER OSHA 29 CFR 1910.23 (e) (8).
- TESTED AND MET REQUIREMENTS AS DESCRIBED IN "STANDARD PRESENTATION TO CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH STANDARDS BOARD - PROPOSED STATE STANDARD, TITLE 8, CHAPTER 4, SECTION 1632 (REPORT NUMBER 3075015-2).

CM - CURB MOUNTED

FTH - FIBERGLASS TRANSLUCENT HIGH

1 - SINGLE GLAZED

- TESTING PERFORMED ON 48"x96" DOME.

Bristolite Daylighting Systems

401 East Goetz Avenue, Santa Ana, CA. 92707 TEL 714.540.8950 / FAX 714.540.5415

;	CUSTOMER:	PREPARED BY:	JOB NO:
	PROJECT:	SUBMITTAL DATE:	ARCHITECT:

165° ○