



**ENERGY STAR CURB MOUNTED LOUVERED  
SMOKE HATCH w/EXTERIOR MANUAL RELEASE**

**\* FUSIBLE LINK TEMPERATURE**  
PLEASE SELECT **ONE**:  
165°  212°  286°  360°

**MODEL: F4896-SHDL-CM-1-FTH-IR-HW-SR-M1-MF**  
NOT TO SCALE

SHDL - ALUM. LOUVERED SMOKE HATCH  
CM - CURB MOUNTED  
1 - SINGLE GLAZED

FTH - FIBERGLASS TRANSLUCENT HIGH  
IR - IMPACT RESISTANT  
HW - HIGH WIND

SR - STORM RESISTANT  
M1 - EXTERIOR MAN. RELEASE  
MF - MILL FINISH

MODEL SIZE	INSIDE CURB DIMENSION	QTY
4896	48" x 96"	

**DOME MATERIAL TESTED IN CONFORMANCE WITH:**  
 - HIGH WIND RESISTANT - DOME OF THIS UNIT HAS EXCEEDED 90 MPH UPLIFT IN TESTING.  
 - BURN RATE - CLASSIFIED AS CC1 MATERIAL.  
 - TESTED AND MET LOAD REQUIREMENTS PER OSHA 29 CFR 1910.23 (e) (8).  
 - TESTED AND MET REQUIREMENTS AS DESCRIBED IN "STANDARD PRESENTATION TO CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH STANDARDS BOARD - PROPOSED STATE STANDARD, TITLE 8, CHAPTER 4, SECTION 1632 (REPORT NUMBER 3075015-2).  
 - TESTING PERFORMED ON 48"x96" DOME.

**\*OPTIONS**  
(NOT SHOWN)  
 BS - BIRD SCREEN  
 DF - DUST FILTER  
 IS - INSECT SCREEN  
 RG - RAIN GUARD

**Bristolite® Daylighting Systems**

401 East Goetz Avenue, Santa Ana, CA. 92707  
TEL 714.540.8950 / FAX 714.540.5415

CUSTOMER :

PROJECT :

PREPARED BY :

SUBMITTAL DATE :

JOB NO :

ARCHITECT :