



TRITUFF ALUMINUM CURB MOUNTED LOUVERED DOUBLE LID SMOKE VENT w/EXTERIOR MANUAL RELEASE

MEETS UBC 15-7 10 PSF.

MODEL : SVDL-L-CM-HS1-MF-OR

NOT TO SCALE

SVDL - ALUMINUM FRAME DOUBLE LID SMOKE VENT
L - LOUVERED
CM - CURB MOUNT
HS1 - TRITUFF DOME

MF - MILL FINISH
OR - EXTERIOR MANUAL RELEASE

MODEL SIZE	ROUGH OPENING DIMENSION	Q'TY.
4848	48" x 48"	
4896	48" x 96"	
6072	60" x 72"	

NOTE: UNIT HAS BEEN TESTED TO OPEN AGAINST 10 lbs./sq.ft. LOAD IN ACCORDANCE WITH UBC 15-7.

DOME MATERIAL TESTED IN CONFORMANCE WITH:

HIGH WIND RESISTANT - DOME OF THIS UNIT HAS EXCEEDED 90 MPH UPLIFT IN TESTING.
BURN RATE - CLASSIFIED AS CC1 MATERIAL

* FUSIBLE LINK TEMP.:
PLEASE SELECT ONE:
165° 286°
212°
OTHER FUSIBLE LINK
TEMPERATURES AVAILABLE:
360° 520°

Bristolite® Daylighting Systems

401 East Goetz Avenue, Santa Ana, CA. 92707
TEL 714.540.8950 / FAX 714.540.5415

CUSTOMER :

PROJECT :

PREPARED BY :

SUBMITTAL DATE :

JOB NO :

SHEET NO.: