



**ENERGY STAR CURB MOUNTED LOUVERED
SMOKE HATCH w/EXTERIOR MANUAL RELEASE**

*** FUSIBLE LINK TEMPERATURE**
PLEASE SELECT **ONE**:
165° 212° 286° 360°

MODEL: F4896-SHDL-CM-1-FTH-IR-HW-SR-M1-MF
NOT TO SCALE

SHDL - ALUM. LOUVERED SMOKE HATCH
CM - CURB MOUNTED
1 - SINGLE GLAZED

FTH - FIBERGLASS TRANSLUCENT HIGH
IR - IMPACT RESISTANT
HW - HIGH WIND

SR - STORM RESISTANT
M1 - EXTERIOR MAN. RELEASE
MF - MILL FINISH

MODEL SIZE	INSIDE CURB DIMENSION	QTY
4896	48" x 96"	

DOME MATERIAL TESTED IN CONFORMANCE WITH:
 - HIGH WIND RESISTANT - DOME OF THIS UNIT HAS EXCEEDED 90 MPH UPLIFT IN TESTING.
 - BURN RATE - CLASSIFIED AS CC1 MATERIAL.
 - TESTED AND MET LOAD REQUIREMENTS PER OSHA 29 CFR 1910.23 (e) (8).
 - TESTED AND MET REQUIREMENTS AS DESCRIBED IN "STANDARD PRESENTATION TO CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH STANDARDS BOARD - PROPOSED STATE STANDARD, TITLE 8, CHAPTER 4, SECTION 1632 (REPORT NUMBER 3075015-2).
 - TESTING PERFORMED ON 48"x96" DOME.

***OPTIONS**
(NOT SHOWN)
 BS - BIRD SCREEN
 DF - DUST FILTER
 IS - INSECT SCREEN
 RG - RAIN GUARD

Bristolite® Daylighting Systems
 401 East Goetz Avenue, Santa Ana, CA. 92707
 TEL 714.540.8950 / FAX 714.540.5415

CUSTOMER :
 PROJECT :

PREPARED BY :
 SUBMITTAL DATE :
 JOB NO :
 ARCHITECT :