



## TRITUFF ALUMINUM CURB MOUNTED SKYLIGHT

**MODEL: FXXXX-S-CM-1-HS1-MF**

NOT TO SCALE

S - ALUMINUM FRAME      HS1 - TRIARCH TRITUFF DOME  
 CM - CURB MOUNTED      MF - MILL FINISH  
 1 - SINGLE GLAZED

MODEL NUMBER	INSIDE CURB DIMENSIONS	QTY
F4848-S-CM	48" x 48"	
F4896-S-CM	48" x 96"	
F6072-S-CM	60" x 72"	

**DOMES MATERIAL TESTED IN CONFORMANCE WITH:**

- HIGH WIND RESISTANT - DOME OF THIS UNIT HAS EXCEEDED 90MPH UPLIFT IN TESTING.
- BURN RATE - TRI-TUFF MATERIAL CLASSIFIED AS CC1 MATERIAL.
- TESTED AND MET LOAD REQUIREMENTS PER OSHA 29 CFR 1910.23 (8).
- TESTED AND MET REQUIREMENTS AS DESCRIBED IN "STANDARD PRESENTATION TO CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH STANDARDS BOARD - PROPOSED STATE STANDARD, TITLE 8, CHAPTER 4, SECTION 1632 (REPORT NUMBER 3075015-1).
- TESTING PERFORMED ON 48"x96" DOME.

**Bristolite® Daylighting Systems**

401 East Goetz Avenue, Santa Ana, CA. 92707  
 TEL 714.540.8950 / FAX 714.540.5415

CUSTOMER :	PREPARED BY :	JOB NO :
PROJECT :	SUBMITTAL DATE :	ARCHITECT :