



**ENERGY STAR CURB MOUNTED LOUVERED
SMOKE HATCH w/EXTERIOR MANUAL RELEASE**

*** FUSIBLE LINK TEMPERATURE**
PLEASE SELECT **ONE**:

165° 212° 286° 360°

MODEL: H4896-SSHDL-CM-1-FTH-IR-HW-SR-M1-MF-RG

NOT TO SCALE

MODEL SIZE	INSIDE CURB DIMENSION	QTY
4896	48" x 96"	

DOME MATERIAL TESTED IN CONFORMANCE WITH:

- HIGH WIND RESISTANT - DOME OF THIS UNIT HAS EXCEEDED 90 MPH UPLIFT IN TESTING.
- BURN RATE - CLASSIFIED AS CC1 MATERIAL.
- TESTED AND MET LOAD REQUIREMENTS PER OSHA 29 CFR 1910.23 (e) (8).
- TESTED AND MET REQUIREMENTS AS DESCRIBED IN "STANDARD PRESENTATION TO CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH STANDARDS BOARD - PROPOSED STATE STANDARD, TITLE 8, CHAPTER 4, SECTION 1632 (REPORT NUMBER 3075015-2).
- TESTING PERFORMED ON 48"x96" DOME.

SSHDL - STEEL LOUVERED SMOKE HATCH
 CM - CURB MOUNTED
 1 - SINGLE GLAZED
 FTH - FIBERGLASS TRANSLUCENT HIGH
 IR - IMPACT RESISTANT
 HW - HIGH WIND
 SR - STORM RESISTANT
 M1 - EXTERIOR MANUAL RELEASE
 MF - MILL FINISH
 RG - RAIN GUARD

Bristolite® Daylighting Systems
 401 East Goetz Avenue, Santa Ana, CA. 92707
 TEL 714.540.8950 / FAX 714.540.5415

CUSTOMER :

PREPARED BY :

JOB NO :

PROJECT :

SUBMITTAL DATE :

ARCHITECT :