



## ENERGY STAR FIBERLITE CURB MOUNTED SKYLIGHT

**MODEL: H48XX-SS-CM-1-FTH-IR-HW-MF**

NOT TO SCALE

SS - GALVANIZED STEEL FRAME  
 CM - CURB MOUNTED  
 1 - SINGLE GLAZED

FTH - FIBERGLASS TRANSLUCENT HIGH  
 IR - IMPACT RESISTANT  
 HW - HIGH WIND

MF - MILL FINISH

MODEL NUMBER	INSIDE CURB DIMENSIONS	QTY
H4848-SS-CM	48"x48"	
H4896-SS-CM	48"x96"	

**DOME MATERIAL TESTED IN CONFORMANCE WITH:**

- HIGH WIND RESISTANT - DOME OF THIS UNIT HAS EXCEEDED 90 MPH UPLIFT IN TESTING.
- BURN RATE - CLASSIFIED AS CC1 MATERIAL.
- TESTED AND MET LOAD REQUIREMENTS PER OSHA 29 CFR 1910.23 (e) (8).
- TESTED AND MET REQUIREMENTS AS DESCRIBED IN "STANDARD PRESENTATION TO CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH STANDARDS BOARD - PROPOSED STATE STANDARD, TITLE 8, CHAPTER 4, SECTION 1632 (REPORT NUMBER 3075015-2).
- TESTING PERFORMED ON 48"x96" DOME.

**Bristolite® Daylighting Systems**

401 East Goetz Avenue, Santa Ana, CA. 92707  
 TEL 714.540.8950 / FAX 714.540.5415

CUSTOMER :

PROJECT :

PREPARED BY :

SUBMITTAL DATE :

JOB NO :

ARCHITECT :