


Nano Insulgel

Super Insulating Silica Aerogel

Industrial Skylight
w/Thermal Barrier Break




Acrylic Dome

Model ALIB

Frame Material: Aluminum
NFRC: Certified
IECC 2015: Meets without controls all climate zones
OSHA: Meets CFR fall regulations
AAMA: WDMA/CSA 101/I.S.2/A440-08 & WDMA/CSA 101/I.S.2/A440-05

Details:



Specifications:

Nano Insulgel skylight shall be model No. _____ as manufactured by Bristolite Daylighting Systems, Santa Ana, CA. Skylights shall be fully factory assembled consisting of an acrylic glazing with a CC-2 classification plus a structural polycarbonate panel filled with nano silica aerogel that is sealed by interior and exterior gaskets to a 6063-T5 heliarc welded aluminum frame fabricated of aluminum with a polyvinyl chloride (PVC) thermal barrier break (UL/FM Code Compliant) to prevent thermal losses through the frame and the formation of condensation on its interior surfaces. The frame is to have an integral condensation channel to carry moisture to the exterior. The aluminum retaining cap fasteners are to be corrosive resistant. The skylight frame shall be installed either on a 1-1/2" wide curb furnished by others or on its own 9", or 12" high self flashing curb fabricated from aluminum with a 2-3/4" roof nailing flange. The base is made up with 1" insulation and a wood nailer and/or an additional aluminum liner on the exterior of the self flashing curb.

Sizes:

Model Number	Inside Curb Dimension	Model Number	Inside Curb Dimension	Model Number	Inside Curb Dimension	Model Number	Inside Curb Dimension
1414-ALIB	14 1/4" x 14 1/4"	6060-ALIB	60" x 60"	2448-ALIB	24" x 48"	3775-ALIB	37" x 75"
1919-ALIB	19" x 19"			2496-ALIB	24" x 96"	3859-ALIB	38" x 59"
2222-ALIB	22 1/4" x 22 1/4"	1422-ALIB	14 1/4" x 22 1/4"	3037-ALIB	30 1/4" x 37"	4669-ALIB	46 1/4" x 69 1/2"
3030-ALIB	30 1/4" x 30 1/4"	1446-ALIB	14 1/4" x 46 1/4"	3046-ALIB	30 1/4" x 46 1/4"	4689-ALIB	46 1/4" x 89 1/2"
3737-ALIB	37" x 37"	2230-ALIB	22 1/4" x 30 1/4"	3069-ALIB	30 1/4" x 69 1/2"	4884-ALIB	48" x 84"
4242-ALIB	42" x 42"	2237-ALIB	22 1/4" x 37"	3096-ALIB	30 1/4" x 96"	4896-ALIB	48" x 96"
4646-ALIB	46 1/4" x 46 1/4"	2246-ALIB	22 1/4" x 46 1/4"	3496-ALIB	34" x 96"	5460-ALIB	54" x 60"
4848-ALIB	48" x 48"	2272-ALIB	22 1/4" x 72"	3696-ALIB	36" x 96"	6072-ALIB	60" x 72"
5555-ALIB	55" x 55"	2296-ALIB	22 1/4" x 96"	3746-ALIB	37" x 46 1/4"		Call for additional sizes

Solar Heat Gain Coefficient = .31, U Factor = .37, Visible Light Transmission = 48% (Typical for CC/CNANO double glazed units)

Features:

- Self Flashing (SF)
 - Two Acrylic Color Choices: Clear Colorless (CC) or Medium White Translucent (WTM)
 - Nano Insulgel Panel Thickness: 10mm, 16mm, 20mm & 25mm
 - Insulated Curb (INS)
 - Wood Nailer (WN)
- Add highlighted suffixes to model number where applicable:
 i.e. **4848-ALIB-SF-2-CC-16mm-CNANO-9-INS-WN-MF**

Options:

- Insulating Double Domes (2)
- Pyramid (P) or Double Hip (DH) Shaped Dome (selected sizes)
- Low Profile Dome (LP) (selected sizes)
- Frame Finish - Bronze Anodize (BA), Clear Anodize (CA), White Painted (WP) or Mill Finish (MF)

Options: (cont.)

- Self Flashing Bases of 9" or 12" (9 or 12)
- Aluminum Double Wall (DW)
- EPDM Curb Seal Tape

Accessories: See PDS (Product Data Sheets) for these Items

- Gladiator
 - Security Grills (SG)
 - Safety Screens (SSCRN)
 - External Safety Cages (SCAGE)