




Bristolite copolyester glazing has been load tested and complies with OSHA – CFR's for fall protection.

### Copolyester Triarch

#### Details (Scale: 1":1'-3")



#### Specifications

Trituff Skylight shall be model No. \_\_\_\_\_ as manufactured by Bristolite Daylighting Systems, Santa Ana, CA. The curb, cross stiffeners & double doors shall be fabricated from 14ga. galvanized steel and shall be glazed with plastic domes using Trituff UL 972 listed material. Corners shall be welded to insure weather tightness. The smoke vent domes come attached to a louvered frame. Louvers will be fixed storm resistant louver blades of galvanized steel and shall be continuous. Double lid domes are compression loaded by torsion springs, secured on the opposite side with actuated latches and equipped with a shock absorber to control the speed of operation operated either manually, or by UL/FM listed fusible links. They can also be opened manually by exterior or interior releases. Doors will open against a 10psf uniform load. In the closed position the units will withstand a minimum 40psf uniform static positive & negative load. Base frame shall be installed on a 1-1/2" wide curb furnished by others or on its own self flashing curb fabricated from galvanized steel with a 3" roof flange. Materials are to be self-extinguishing Approved Plastic CC-1 Rated. Unit meets the requirements of UBC Standard 15-7. Manufactured & tested to UL 793.

#### Sizes:

Model Number	Inside Curb Dimension	Approx. Amount of Free Air Space in Sq. Ft.
4848-ECO-SVSHL	48" x 48"	6.0

Model Number	Inside Curb Dimension	Approx. Amount of Free Air Space in Sq. Ft.
4896-ECO-SVSHL	48" x 96"	9.0
6072-ECO-SVSHL	60" x 72"	8.0

Solar Heat Gain Coefficient = .50, U Factor = .65, Visible Light Transmission = 60% (Typical for HS1 double glazed units)

#### Features:

- Curb Mounted (CM) or Self Flashing (SF)
- White Copolyester Glazing (HS1)
- Exterior and/or Interior Manual Releases (M1, M2 or M3)
- Fusible Link Temperatures: 165°, 212°, 286°, 360° or 520°  
Add highlighted suffixes to model number where applicable:  
i.e. 4896-ECO-SVSHL-CM-1-HS1-M1

#### Options:

- Self Flashing Bases of 9" or 12" (9 or 12)
- Insulated Frame (INS)
- Double Wall Frame (DW)
- Insect Screens (IS) or Bird Screens (BS)
- Rain Guard (RG) and/or Dust Filters (DF)

#### Accessories: See PDS (Product Data Sheets) for these Items

- Gladiator
  - Structural Curb (SC)
  - Security Grills (SG)
  - Safety Screens (SSCRN)
- Quickkit (Installation Kits)
  - Stainless Steel (QKSS)
  - Zinc Plated (QKZP)