



TRITUFF ALUMINUM CURB MOUNTED DOUBLE LID SMOKE VENT

MODEL: SVDL-CM-HS1-OR-MF

NOT TO SCALE

SVDL - ALUMINUM FRAME DOUBLE LID SMOKE VENT
 CM - CURB MOUNTED
 HS1 - TRITUFF DOME

OR - OUTSIDE MANUAL RELEASE
 MF - MILL FINISH

NOTES: - UNIT HAS BEEN TESTED TO OPEN AGAINST 10 LBS./SQ.SF. LOAD IN ACCORDANCE WITH UBC 15-7.
 - THIS UNIT COMPLIES WITH SECTION 906 OF THE UBC-1997 AND IS INCLUDED IN EVALUATION REPORT ER-5150 (AVAILABLE ONLINE AT www.icc-es.org).

* FUSIBLE LINK TEMP.:
 PLEASE SELECT ONE:
 165° 286°
 212°

MODEL NUMBER	INSIDE CURB DIMENSIONS	QTY
4848-SVDL-CM	48" x 48"	
4896-SVDL-CM	48" x 96"	
6072-SVDL-CM	60" x 72"	

DOMES MATERIAL TESTED IN CONFORMANCE WITH:
 - HIGH WIND RESISTANT-DOME OF THIS UNIT HAS EXCEEDED 90MPH UPLIFT IN TESTING
 - BURN RATE-CLASSIFIED AS CC1 MATERIAL

OTHER FUSIBLE LINK TEMPERATURES AVAILABLE:
 360° 520°

Bristolite Daylighting Systems
 401 East Goetz Avenue, Santa Ana, CA. 92707
 TEL 714.540.8950 / FAX 714.540.5415

CUSTOMER :	PREPARED BY :	JOB NO :
PROJECT :	SUBMITTAL DATE :	ARCHITECT :