



TRITUFF STEEL CURB MOUNTED LOUVERED SKYLIGHT

MODEL: TXXXX-SSL-CM-HS1-MF

SSL – GALVANIZED STEEL FRAME LOUVERED
 CM – CURB MOUNTED
 HS1 – TRITUFF TRIARCH DOME

MF – MILL FINISH

NOT TO SCALE

MODEL NUMBER	INSIDE CURB DIMENSIONS	QTY
4848-SSL-CM	48" x 48"	
4896-SSL-CM	48" x 96"	

DOME MATERIAL TESTED IN CONFORMANCE WITH:

- HIGH WIND RESISTANT - DOME OF THIS UNIT HAS EXCEEDED 90MPH UPLIFT IN TESTING.
- BURN RATE - TRI-TUFF MATERIAL CLASSIFIED AS CC1 MATERIAL.
- TESTED AND MET LOAD REQUIREMENTS PER OSHA 29 CFR 1910.23 (e) (8).
- TESTED AND MET REQUIREMENTS AS DESCRIBED IN "STANDARD PRESENTATION TO CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH STANDARDS BOARD - STATE STANDARD, TITLE 8, CHAPTER 4, SECTION 1632 (REPORT NUMBER 3075015-1).
- TESTING PERFORMED ON 48"x96" TRI-ARCH DOME.

Bristolite® Daylighting Systems
 401 East Goetz Avenue, Santa Ana, CA. 92707
 TEL 714.540.8950 / FAX 714.540.5415

CUSTOMER :	PREPARED BY :	JOB NO :
PROJECT :	SUBMITTAL DATE :	SHEET NO.: