



Re-Cover Board-3

Rmax Re-Cover Board-3 is an energy-efficient thermal insulation board composed of a closed-cell polyiso foam core with facings on both sides. It utilizes a CFC-, HCFC-, and HFC-free blowing agent that has zero Ozone Depletion Potential (ODP) and negligible Global Warming Potential (GWP).

COMPLIANCES:

- ASTM C1289 Type II
- International Building Code (IBC), Section 2603
- International Energy Conservation Code (IECC) and ASHRAE 90.1
- Miami-Dade County Product Control Approved
- City of Los Angeles Research Report
- California Code of Regulations, Title 24

“R” means resistance to heat flow. The higher the R-value, the greater the insulating power. Please note: To get the marked R-value, it is essential that this insulation product be installed properly. Installation instructions are not included with this package. Contact Rmax Sales for instructions and guidelines.

CAUTION: The plastic wrapping is not intended as protection from weather.

CAUTION: A nuisance dust may be created by cutting this product. Rmax recommends that a suitable respirator be worn during the cutting of this foam product.

WARNING: The polyisocyanurate foam core of this product is combustible. Exposure to heat/flame sources of sufficient intensity, such as a welder’s torch, may cause this product to burn.



Intertek

Listed Building Products

Polyisocyanurate Insulation Board

W/N 14912

Tested per ASTM E84 (foam core only)



Subject to the conditions of approval as a roof insulation when installed as described in the current edition of the FM Global RoofNav.

Nominal Thickness	1.0
LTTR-Value	5.7
Pieces/Package	48
Panel Size	48X96
Sq. Ft./Package	1536
Production Code	F1/2/2/2015
Bundle	#11

PE

1.0

Rmax Operating, LLC
13524 Welch Road
Dallas, TX 75244
(800) 527-0890

Rmax Operating, LLC
1649 S. Batesville Road
Greer, SC 29650
(800) 845-4455

Rmax Operating, LLC
210 Lyon Drive
Fernley, NV 89408
(800) 762-9462